

DIAPRO MARINE

AN **ALM**RED TRADEMARK



SOLUTION, INNOVATION, SERVICE

WATER TREATMENT
CLEANING & MAINTENANCE
DEPOLLUTION

WATER TREATMENT

BOILER TREATMENT

DIAPROSIM™ B115

Alkalisant agent and dispersant for boilers of all pressures

25kg jerrycan / 250kg drum

DIAPROSIM™ CIP0

Regulation of pH and water hardness

25kg bucket

DIAPROSIM™ VN11

Corrosion inhibitor for condensate return lines

20kg jerrycan / 200kg drum

DIAPROSIM™ 820 / 830 / 840

Oxygen scavenger for boilers of low and medium pressure

25kg jerrycan

DIAPROSIM™ B120 / B130

Oxygen scavenger for average and high pressure boilers (without hydrazine)

20kg jerrycan / 200kg drum

TREATMENT OF CLOSED CIRCUITS / DIESEL ENGINES

DIAPROSIM™ RD15 / RD30 (liquid) or RD11 (powder) *

Corrosion inhibitor based on nitrite for closed circuits, ice/chilled water circuits and Diesel engines

80kg/25kg jerrycan / 200 kg / 250 kg drum
25kg bucket

DIAPROSIM™ RD25 *

Corrosion and scaling inhibitor for closed circuits and Diesel engines (Aluminium protection)

25kg jerrycan / 250kg drum

DIAPROSIM™ EC10N

Corrosion and scaling inhibitor for closed circuits

25kg jerrycan / 250kg drum

DIAPROSIM™ RDH

Antifreeze with inhibitor for closed circuits and Diesel engines

60kg drum / 225kg drum

* Recommended by engine manufacturers





WATER TREATMENT

TREATMENT OF EVAPORATORS / SEAWATER

DIAPROSIM™ B113

Anti-scale and anti-foam treatment for seawater evaporators

20kg jerrycan / 200kg drum

REVERSE OSMOSIS TREATMENT

DIAPROSIM™ RO-A

COMPLEMENT TO RO-B

Reverse osmosis membrane acid cleaner

20kg jerrycan

DIAPROSIM™ RO-B

COMPLEMENT TO RO-A

Reverse osmosis membrane alkaline cleaner

25kg jerrycan

DIAPROSIM™ RO-113

Scale inhibitor for reverse osmosis membranes

20kg jerrycan / 200kg drum

ACID CLEANING

DIAPROSIM™ RD13

Cleaner for scaled equipment

25kg bucket

DIAPROSIM™ DH32

Rust elimination

25kg jerrycan

DIAPROSIM™ DH9

Hydrochloric acid

25kg jerrycan

EQUIPMENT

- **Water production machine station :**
Filtration - softener pouches
- **Neutralisation / Mineralisation station:**
Neutralisation / mineralisation filters
- **Chlorination station**
- **Etc.**

BIOCIDE

DIAPROSIM™ FB9A3

Algaecide and bactericide for closed, open and semi-open circuits (quaternary ammonium)

20kg jerrycan / 200kg drum

SPECIFIC APPLICATIONS

DIAPROSIM™ DPL50

Corrosion inhibitor
Sanitary hot water - drinking water

25kg jerrycan / 250kg drum

DIAPROSIM™ TSB

Anti-foam - Protection of boilers
20kg jerrycan



CONSUMABLES

MINERALITE

Remineralisation of drinking water.
Elimination of iron and lead

25kg bag

NEUTRALITE

Neutralisation of the pH of distilled water before distribution in drinking water circuits

25kg bag

ION EXCHANGER RESINS

Treatment of drinking water.
Mixed bed

25 L bag

*Non-exhaustive selection of products.
Please consult us for more information.*



DEPOLLUTION

ABSORBANTS

ROLLS, SINGLE, WHITE

Rolls, Monolayer structure with high absorption capacity, white hydrocarbons. Single thickness.

- Box of 2 rolls. Roll of 0.40mx60m
Pre-cut in width
Absorption power: 162L (AFNOR)
- Box of 1 roll. Roll of 0.80mx60m
Pre-cut in width and length
Absorption power : 162L (AFNOR)
- Bag of 2 rolls. Roll of 0.40mx60m
Not pre-cut
Absorption power : 162L (AFNOR)
- Bag of 1 roll. Roll of 0.80mx60m
Not pre-cut
Absorption power : 162L (AFNOR)

ROLLS, DOUBLE, WHITE

Rolls, Monolayer structure with high absorption capacity, white hydrocarbons. Double thickness.

- Box of 2 rolls. Roll of 0.40mx40m
Pre-cut in width
Absorption power : 180L (AFNOR)
- Box of 1 roll. Roll of 0,80mx40m
Pre-cut in width and length
Absorption power : 180L (AFNOR)
- Bag of 2 rolls. Roll of 0,40mx40m
Not pre-cut
Absorption power : 180L (AFNOR)
- Bag of 1 roll. Roll of 0,80mx40m
Not pre-cut
Absorption power : 180L (AFNOR)

SHEETS, SINGLE, WHITE

Rolls, Monolayer structure with high absorption capacity, white hydrocarbons. Single thickness. Pre-cut in width

- Bag of 50 sheets. Sheets of 40x50cm
Absorption power : 34L (AFNOR)
- Box of 200 sheets. Sheets of 40x50cm
Absorption power : 135L (AFNOR)
- Box of 4 packets of 50 sheets.
Sheets de 40x50cm.
Absorption power : 135L (AFNOR)

SHEETS, DOUBLE, WHITE

Sheets, Monolayer structure with high absorption capacity, white hydrocarbons. Double thickness. Pre-cut in width

- Box of 100 sheets. Sheets of 40x50cm
Absorption power : 113L (AFNOR)
- Box of 2 packets of 50 sheets.
Sheets of 40x50cm.
Absorption power : 113L (AFNOR)
- Bag of 100 sheets. Sheets of 30x30cm.
Absorption power : 51L (AFNOR)

PURE FIBRE BARRIERS

- Absorption power : 252L (AFNOR)
Ø 13cmx3m, bag of 4 barriers
- Absorption power : 210L (AFNOR)
Ø 13cmx5m, bag of 2 barriers
- Absorption power : 396L (AFNOR)
Ø 20cmx3m, bag of 4 barriers
- Absorption power : 330L (AFNOR)
Ø 20cmx5m, bag of 2 barriers

BOOMS IN FLAKES

- Absorption power : 106L (AFNOR)
Ø 8cmx1,20m, • Box of 20 booms
- Absorption power : 106L (AFNOR)
Ø 8cmx3m, • Box of 8 booms
- Absorption power : 79L (AFNOR)
Ø 8cmx18m, • Box of 1 boom

CARBONISED DIATOMACEOUS EARTH

- 20kg bag
- 15kg bucket

*Non-exhaustive selection of products.
Please consult us for more information.*





DEPOLLUTION

CONTAINMENT BARRIER

CYLINDRICAL FLOATS

- Containment barrier with cylindrical floats. Round closed-cell foam with PVC-coated polyester fabric. Total height 450 mm. Air draft 150 mm + water draft 300 mm. Aluminium ASTM connectors of type Z at the extremities, ballast chain at the bottom of the skirt. Length 25 m, orange colour, weight for 1 m: 3.2 kg, total weight 80 kg.
- Containment barrier with cylindrical floats. Round closed-cell foam with PVC-coated polyester fabric. Total height 600 mm. Air draft 250 mm + water draft 350 mm. Aluminium ASTM connectors of type Z at the extremities, ballast chain at the bottom of the skirt. Length 25 m, orange colour, weight of 1 m: 4.1 kg, total weight 102.5 kg.

FLAT CURTAIN

- Flat curtain type containment barrier. Thin closed-cell foam with PVC-coated polyester fabric. Total height 450 mm. Air draft 150 mm + water draft 300 mm. Length 25 m. Aluminium ASTM connectors of type Z at the ends, ballast chain at the bottom of the skirt. Orange colour, weight of 1 m: 2.7 kg, total weight 67.5 kg.
- Flat curtain type containment barrier. Thin closed-cell foam with PVC-coated polyester fabric. Total height 650 mm. Air draft 250 mm + water draft 400 mm. Aluminium ASTM connectors of type Z at the extremities, ballast chain at the bottom of the skirt. Length: 25 m, orange colour, weight for 1 m: 3.9 kg, total weight 97.5 kg.

SPILL KIT

SPILL KIT 50L

content :
35 double thickness sheets 40x50cm
2 booms 8cmx1,20m
10 wiping sheets 32x38cm
1 pair of nitrile gloves
2 recovery bags 50L

- In PVC transparent bag (560x460x220cm)
- In opaque robust kit (580x390x330mm)

SPILL KIT 100L

content :
50 double thickness sheets 40x50cm
2 booms 8cmx3m
2 cushions 40x40cm
15 wiping sheets 32x38cm
1 pair of nitrile gloves
1 pair of safety-goggles
2 recovery bags 100L

- in 120 litre barrel PE with total opening (492x800mm hauteur)
- in rigid green plastic box 185L (842x602x660mm hauteur)
- in 2-wheel container 120L (480x540x940mm hauteur)
- in PE storage cabinet with lock (545x440x990mm hauteur)



CLEANING & MAINTENANCE

DETERGENTS

DT DAILYSAFE

Multi-use detergent for frequent cleaning, non-flammable, for all materials, biodegradable, no toxic compounds, no solvents, ultra-sonic application too, pH in pure form : 11, blue, scent: pine

5kg jerrycan / 20Kg jerrycan / 200kg drum

DT ENVIRO CLEANER

Multi-use detergent, non-flammable, biodegradable > 90%, 22% active ingredients. Low to high foaming, pH in pure form : 12.8, pink, odourless

5kg jerrycan / 20Kg jerrycan / 200kg drum

DT NET

Multi-use detergent, multi-surfaces, agri-food
Low to high foaming,
pH in pure form : 13.6, yellow,
scent : fresh mint

5kg jerrycan / 20Kg jerrycan / 200kg drum

DT MECALUB

Mechanical degreasing detergent, biodegradable > 90%, anti-corrosion. Low to high foaming, pH in pure form : 13.2, pink, odourless

5kg jerrycan / 20Kg jerrycan / 200kg drum

DT HP

Concentrated degreasing detergent, specially formulated for difficult cleaning, 40% active ingredients. Non-foaming, pH in pure form: 13.7, blue, scent: menthol

5kg jerrycan / 20Kg jerrycan / 200kg drum

DT BIOSUR HD

Safe, highly concentrated, versatile multi-purpose detergent, biodegradable > 90% No pictogram (CLP)

5kg jerrycan / 20Kg jerrycan / 200kg drum

DEGREASING AGENTS

DG BIORIG

Solvent degreasing agent of plant origin, emulsifiable, no VOC, special platform (Rigwash) Emulsifiable.
KB index > 180 Flashpoint > 170°C, Biodegradable 100%

5L jerrycan / 20L jerrycan / 200L drum

DG SOLVELEC

Dielectric solvent degreaser, no benzene, aromatics, chlorine or glycol. Insoluble. KB index: 36, Flashpoint: 64°C, evaporation rate: 110', breakdown voltage: 63,000 V

5L jerrycan / 20L jerrycan / 200L drum

DG MULTISOLV

Multi-purpose solvent degreaser at quick evaporation, no benzene, aromatics, chlorine or glycol. Partially soluble.
KB index: 90, Flashpoint: 24°C, evaporation rate: 9'

5L jerrycan / 20L jerrycan / 200L drum

DG DEWATERING

Solvent degreaser with "dewatering effect". Not soluble.
KB index: 52, Flashpoint: 58°C, evaporation rate: 80', breakdown voltage: 60,000V

5L jerrycan / 20L jerrycan / 200L drum

DG MOTORSOLV

Solvent based degreaser "formulated for engines" pine terpene based, no benzene, chlorine or glycol. Emulsifiable. KB index: 90, Flashpoint: 62°C, evaporation rate: 110'

5L jerrycan / 25L mini-barrel / 200L drum

DG CARBONSOLV

Solvent degreasing cleaner with enhanced solvent power. Specially formulated for difficult cleaning, particularly for the elimination of calcinated grease, calophane solder flux, traces of carbon, etc. Partially soluble. KB index: 117, Flashpoint: (not measurable), Evaporation speed: 15'

5L jerrycan / 25L mini-barrel / 200L drum

DG CLEANSOLV

Emulsifiable solvent based degreaser, specially formulated for cleaning of burners and heating units. Emulsifiable. KB index: 215, Flashpoint: 46°C, evaporation rate: 18'

5L jerrycan / 20L jerrycan / 200L drum





CLEANING & MAINTENANCE

METAL PROTECTION

PROTECTSOLV

Anti-corrosion oil-film protector in the marine environment,
-50°C to +40°C
Insoluble, Flashpoint: 64°C,
Anti-corrosion protection
(salt spray test: NFX 41002: 110h)
breakdown voltage: 60,000V

5L jerrycan / 20L jerrycan / 200L drum

D-ROUILLE

Rust converter

5L jerrycan

PENETRATING OILS - ASSEMBLING PASTES

DEGRIP TEF

Teflon-based penetrating lubricant - aerosols

Aerosol 650ml

DEGRIP ENVIRO10

Biodegradable penetrating lubricant,
no VOC, 10 functions,
plant-based formula - aerosols

Aerosol 650ml

ALUPATE

Aluminium-based assembly paste

Aerosol 650ml

DIESEL ENGINE PROTECTION

AF 1374 BIO

Protective bactericidal treatment
for medium-term hydrocarbons
(Diesel, fuel, kerosene)

5L jerrycan / 30L drum / 200L drum

YOUR CONTACT

+33 (0)3 80 97 36 29

diapromarine@almred.com

www.almred.com





DIAPRO MARINE

AN **ALMRED** TRADEMARK



**WATER TREATMENT
DEPOLLUTION
CLEANING & MAINTENANCE**

YOUR CONTACT

+33 (0)3 80 97 36 29

diapromarine@almred.com

www.almred.com

solution, innovation, service